

# SP-S913-M / SP-C913-M

智能模板机  
Intelligent template machine



## 性能优势

采用智能闭环缝制系统，实时监控缝制状态，以反馈交互的方式，调控缝制系统。

采用RFID先进芯片识别技术，反应更加快速、灵敏和准确。

采用首创重力式旋梭供油机构，从根本上，保证供油力恒定，保证供油的稳定性。

采用大行程针杆机构，机针高度达22mm，在不同厚度的模板或布料的缝制，应用上，适用性更广泛。

采用智能机械压脚，在具备了智能控制系统的灵活性，同时也具备了机械结构稳定性。

采用丝杠传动系统，结合闭环电机，缝制精度达0.1毫米级别。

选购功能装置：激光切割、振动刀切割、丝杆模组、自动起缝装置

## 效率

通过电脑控制，缝品线迹稳定标准，花样如出一辙，从根本改变了缝制工艺，极大的提升了缝制效益和质量。

## 适用范围

采用智能闭环控制系统，擅长于缝制花样特别复杂的产品。

## Advantages

The intelligent closed-loop sewing system is adopted to monitor sewing operation in real time and to control the sewing operation by means of feedback interaction.

RFID advanced chip identification technology, easy to use, more rapid and accurate response.

Using gravity-type rotary hook oil supply technology, which ensures the constant oil supply and the stability.

Large stroke needle rod mechanism, needle height up to 22mm, enable to use for different thickness of fabrics and for different sewing application.

The intelligent mechanical presser foot has the flexibility of an intelligent control system and the stability of the mechanical structure.

Using screw rod with motor control, sewing accuracy can reach to 0.1 mm.



Optional: laser cutting, vibration knife cutting, double screw rods, automatic sewing function

## Efficiency

Through computer control, the stitches of the sewing product are stable to the standard and the pattern is exactly the same, which fundamentally changes the sewing process and greatly improves the sewing efficiency and quality.

## Application

It adopts intelligent closed-loop control system and is good at sewing products with particularly complicated patterns.



视频及资料下载  
Video and data download

|                             |                          |                 |                         |
|-----------------------------|--------------------------|-----------------|-------------------------|
| 最高缝纫速度 Highest sewing speed | 3500rpm                  | 气压 Air pressure | 0.5Mpa、1.8L/min         |
| 缝制范围 Sewing range           | 1300×850mm               | 重量 Weight       | 540Kg                   |
| 机针型号 Needle model           | Dpx17                    | 外型尺寸 Dimensions | 2250×2200×1300mm(L×W×H) |
| 电压 Voltage                  | 单相 Single phase 200-240V |                 |                         |

以上基础参数表为标准款机型